




BS-260M Dual-Mitering Gear-Driven Bandsaw, 1Ph 220V

Product Images





Short Description

Gear Driven Band Saw - BS-260M

Additional Information

Blade Guide Carbide x Roller Blade Speeds (SFPM) 66-280 Variable Capacity Round 90 X 45 X 60 X 45 8.66" / 5.9" / 3.5" / 5.31" Capacity Square 90 X 45 X 60 X 45L 8.46" / 5.7" / 3.34" / 4.33" Descent Control Hydraulic Drive Gear Input Power 220V 1-Phase Type of Miter Adjustment Dual Swivel Head Miter Angle Range (Deg.) 0 - 60°, 45°L Model Number BS-260M Motor (HP) High Torque 1.1Kw (AC) Prop 65 Cancer and Reproductive Harm Return Manual Shipping Dimensions (L x W x H) (In.) 69x44x45 Table Height (In.) 35" Weight (Lbs.) 745		
Blade Speeds (SFPM) Gearcity Round 90 X 45 X 60 X 45 Refurn Blade Speeds (SFPM) 66-280 Variable 8.66" / 5.9" / 3.5" / 5.31" Capacity Square 90 X 45 X 60 X 45L 8.46" / 5.7" / 3.34" / 4.33" Descent Control Hydraulic Drive Gear Input Power 220V 1-Phase Type of Miter Adjustment Dual Swivel Head Miter Angle Range (Deg.) 0 - 60°, 45°L Model Number BS-260M Motor (HP) High Torque 1.1Kw (AC) Prop 65 Cancer and Reproductive Harm Return Manual Shipping Dimensions (L x W x H) (In.) 69x44x45 Table Height (In.)	Stock Number	BA9-1001432
Capacity Round 90 X 45 X 60 X 45 Capacity Square 90 X 45 X 60 X 45L B.46" / 5.7" / 3.34" / 4.33" Descent Control Hydraulic Drive Gear Input Power 220V 1-Phase Type of Miter Adjustment Dual Swivel Head Miter Angle Range (Deg.) 0 - 60°, 45°L Model Number BS-260M Motor (HP) High Torque 1.1Kw (AC) Prop 65 Cancer and Reproductive Harm Return Manual Shipping Dimensions (L x W x H) (In.) 69x44x45 Table Height (In.)	Blade Guide	Carbide x Roller
Capacity Square 90 X 45 X 60 X 45L Descent Control Hydraulic Drive Gear Input Power 220V 1-Phase Type of Miter Adjustment Dual Swivel Head Miter Angle Range (Deg.) Model Number BS-260M Motor (HP) High Torque 1.1Kw (AC) Prop 65 Cancer and Reproductive Harm Return Manual Shipping Dimensions (L x W x H) (In.) 69x44x45 Table Height (In.)	Blade Speeds (SFPM)	66–280 Variable
Descent Control Drive Gear Input Power 220V 1-Phase Type of Miter Adjustment Dual Swivel Head Miter Angle Range (Deg.) 0 - 60°, 45°L Model Number BS-260M Motor (HP) High Torque 1.1Kw (AC) Prop 65 Cancer and Reproductive Harm Return Manual Shipping Dimensions (L x W x H) (In.) 69x44x45 Table Height (In.)	Capacity Round 90 X 45 X 60 X 45	8.66" / 5.9" / 3.5" / 5.31"
Drive Gear Input Power 220V 1-Phase Type of Miter Adjustment Dual Swivel Head Miter Angle Range (Deg.) 0 - 60°, 45°L Model Number BS-260M Motor (HP) High Torque 1.1Kw (AC) Prop 65 Cancer and Reproductive Harm Return Manual Shipping Dimensions (L x W x H) (In.) 69x44x45 Table Height (In.) 35"	Capacity Square 90 X 45 X 60 X 45L	8.46" / 5.7" / 3.34" / 4.33"
Input Power Type of Miter Adjustment Dual Swivel Head Miter Angle Range (Deg.) 0 - 60°, 45°L Model Number BS-260M Motor (HP) High Torque 1.1Kw (AC) Prop 65 Cancer and Reproductive Harm Return Manual Shipping Dimensions (L x W x H) (In.) 69x44x45 Table Height (In.)	Descent Control	Hydraulic
Type of Miter Adjustment Dual Swivel Head Miter Angle Range (Deg.) 0 - 60°, 45°L Model Number BS-260M Motor (HP) High Torque 1.1Kw (AC) Prop 65 Cancer and Reproductive Harm Return Manual Shipping Dimensions (L x W x H) (In.) 69x44x45 Table Height (In.)	Drive	Gear
Miter Angle Range (Deg.) 0 - 60°, 45°L Model Number BS-260M Motor (HP) High Torque 1.1Kw (AC) Prop 65 Cancer and Reproductive Harm Return Manual Shipping Dimensions (L x W x H) (In.) 69x44x45 Table Height (In.)	Input Power	220V 1-Phase
Model NumberBS-260MMotor (HP)High Torque 1.1Kw (AC)Prop 65Cancer and Reproductive HarmReturnManualShipping Dimensions (L x W x H) (In.)69x44x45Table Height (In.)35"	Type of Miter Adjustment	Dual Swivel Head
Motor (HP) High Torque 1.1Kw (AC) Prop 65 Cancer and Reproductive Harm Return Manual Shipping Dimensions (L x W x H) (In.) 69x44x45 Table Height (In.)	Miter Angle Range (Deg.)	0 – 60°, 45°L
Prop 65 Cancer and Reproductive Harm Return Manual Shipping Dimensions (L x W x H) (In.) 69x44x45 Table Height (In.) 35"	Model Number	BS-260M
Return Manual Shipping Dimensions (L x W x H) (In.) 69x44x45 Table Height (In.) 35"	Motor (HP)	High Torque 1.1Kw (AC)
Shipping Dimensions (L x W x H) (In.) 69x44x45 Table Height (In.) 35"	Prop 65	Cancer and Reproductive Harm
Table Height (In.) 35"	Return	Manual
	Shipping Dimensions (L x W x H) (In.)	69x44x45
Weight (Lbs.) 745	Table Height (In.)	35"
	Weight (Lbs.)	745

