



DP-4016B-VS - 16" Variable Speed Bench Top Drill Press

Product Images



Short Description

Additional Information

Stock Number	BA9-1228213
Base Size (In.)	10.63" x 10.03"
Chuck Size (In.)	.03" - .625" (B16)
Column Diameter (In.)	2-3/4
Distance Base to Spindle (Min.) (In.)	22.83
Drilling Capacity Mild Steel (In.)	3/4
Headstock Movement	Yes (360 degrees)
Horse Power (HP)	0.7500
Input Power	110 Volt
Model Number	DP-4016B-VS
Number of Spindle Speeds	Variable
Overall Dimensions (L x W x H) (In.)	29.13" x 17.52" x 41.33"
Prop 65	Cancer and Reproductive Harm
Range of Spindle Speeds (RPM)	0-2100
Shipping Dimensions (L x W x H) (In.)	48" x 30" x 21"
Spindle Distance to Table (Max.) (In.)	13.18"
Spindle Taper	MT2
Spindle Travel (In.)	3.93"
Swing (In.)	16"
Table Material	Cast Iron
Table Size (In.)	11.14" x 9.76"
Table T-Slot (In.)	2 @ .531"
Table Tilt (Deg.)	L or R 45 Degrees
Tapping Capacity Mild Steel (In.)	1/2"
Warranty	1 Year

Weight (Lbs.)	275
Working Load Limit (Lbs.)	132
Gross Weight	270.0
Distance From Spindle To Base (In.)	22.83
Shipping Weight (Lbs.)	275

