



# Metal Lathe - PL-1860E

## Product Images

---



## Short Description

---

## Additional Information

---

Stock Number	BA9-1016624
Center Distance (In.)	60"
Input Power	220V / 3-phase
Lead Screw Diameter	1.125
Leadscrew Thread Pitch	4 T.P.I.
Longitudinal Feed Imp Qty Type	122 / .0015"-.0913" / rev.
Model Number	PL-1860E-1.0
Modular Pitch Threads Range	21 / .25 to 10 M.P
Motor (HP)	7.5 hp
Nose Radius (In.)	D1-8
Number of Spindle Speeds	25-1800 rpm
Prop 65	Cancer and Reproductive Harm
Quill Taper	MT7
Shipping Dimensions (L x W x H) (In.)	116x45x66
Spindle Bore (In.)	3.125"
Spindle Taper with Sleeve	MT5
Swing Over Bed (In.)	18"
Swing Over Cross Slide (In.)	10-3/4"
Swing Through Gap (In.)	27.5"
Tailstock Spindle Travel (In.)	6"
Warranty	1 Year
Weight (Lbs.)	5650
Width of Bed (In.)	13-1/8"
Gross Weight	5650.0
Compound Rest Travel	5-1/8"

Cross Slide Travel	10-1/2"
Threads Diametrical Quality Type (D.P.)	45 / 3-1/2 to 96 D.P
Threads Imperial Quality Type (T.P.I.)	61 / 1-5/8 to 72 T.P.I

